Membership   Publications/Services   Standards   Conferences   Careers/Jobs

IEEE Xplore®
RELEASE 1.8

Welcome
United States Patent and Trademark Office

IEEE *Xplore*®
1 Million Documents
1 Million Users

» **Search Results**

Help   FAQ   Terms   IEEE Peer Review   **Quick Links** ▽

Welcome to IEEE Xplore®

- ○ Home
- ○ What Can I Access?
- ○ Log-out

Tables of Contents

- ○ Journals & Magazines
- ○ Conference Proceedings
- ○ Standards

Search

- ○ By Author
- ○ Basic
- ○ Advanced

Member Services

- ○ Join IEEE
- ○ Establish IEEE Web Account
- ○ Access the IEEE Member Digital Library

IEEE Enterprise

- ○ Access the IEEE Enterprise File Cabinet

🖳 Print Format

Your search matched **144** of **1047691** documents.
A maximum of **500** results are displayed, **15** to a page, sorted by **Relevance** in **Descending** order.

Refine This Search:
You may refine your search by editing the current search expression or entering a new one in the text box.

| riccati and kalman | Search |

☐ Check to search within this result set

Results Key:
JNL = Journal or Magazine   **CNF** = Conference   **STD** = Standard

1 **Connection between the three-block generalized Riccati equation and the standard Riccati equation**
Darouach, M.; Zasadzinski, M.; Bassong-Onana, A.;
Automatic Control, IEEE Transactions on , Volume: 39 , Issue: 8 , Aug. 1994
Pages:1755 - 1758

[Abstract]   [PDF Full-Text (300 KB)]   **IEEE JNL**

2 **LQG control design for LPV systems**
Fen Wu; Packard, A.;
American Control Conference, 1995. Proceedings of the , Volume: 6 , 21-23 June 1995
Pages:4440 - 4444 vol.6

[Abstract]   [PDF Full-Text (392 KB)]   **IEEE CNF**

3 **Multivariable frequency response methods for colored-noise optimal Kalman filter**
Arcasoy, C.C.;
American Control Conference, 1995. Proceedings of the , Volume: 1 , 21-23 June 1995
Pages:1 - 6 vol.1

[Abstract]   [PDF Full-Text (328 KB)]   **IEEE CNF**

4 **A prefiltering version of the Kalman filter with new numerical integration formulas for Riccati equations**
Womble, M.; Potter, J.;
Automatic Control, IEEE Transactions on , Volume: 20 , Issue: 3 , Jun 1975
Pages:378 - 381

[Abstract]   [PDF Full-Text (432 KB)]   **IEEE JNL**

---

5 An exact solution of the time-invariant discrete Kalman filter
Orfanidis, S.;
Automatic Control, IEEE Transactions on , Volume: 27 , Issue: 1 , Feb 1982
Pages:240 - 242

[Abstract]   [PDF Full-Text (312 KB)]   **IEEE JNL**

---

6 Fast converging and low complexity adaptive filtering using an averaged Kalman filter
Wigren, T.;
Signal Processing, IEEE Transactions on [see also Acoustics, Speech, and Signal Processing, IEEE Transactions on] , Volume: 46 , Issue: 2 , Feb. 1998
Pages:515 - 518

[Abstract]   [PDF Full-Text (204 KB)]   **IEEE JNL**

---

7 An alternate calculation of the discrete-time Kalman filter gain and Riccati equation solution
Leland, R.;
Automatic Control, IEEE Transactions on , Volume: 41 , Issue: 12 , Dec. 1996
Pages:1817 - 1819

[Abstract]   [PDF Full-Text (232 KB)]   **IEEE JNL**

---

8 Kalman filtering and Riccati equations for descriptor systems
Nikoukhah, R.; Willsky, A.S.; Levy, B.C.;
Automatic Control, IEEE Transactions on , Volume: 37 , Issue: 9 , Sept. 1992
Pages:1325 - 1342

[Abstract]   [PDF Full-Text (1340 KB)]   **IEEE JNL**

---

9 New methods for optimal control and filtering of singularly perturbed linear discrete stochastic systems
Lim, M.T.; Gajic, Z.; Shen, X.;
American Control Conference, 1995. Proceedings of the , Volume: 1 , 21-23 June 1995
Pages:534 - 538 vol.1

[Abstract]   [PDF Full-Text (384 KB)]   **IEEE CNF**

---

10 New method for optimal control and filtering of weakly coupled linear discrete stochastic systems
Aganovic, Z.; Gajic, Z.; Shen, X.;
Decision and Control, 1994., Proceedings of the 33rd IEEE Conference on , Volume: 1 , 14-16 Dec. 1994
Pages:1 - 6 vol.1

[Abstract]   [PDF Full-Text (380 KB)]   **IEEE CNF**

---

11 On the 3-block generalized Riccati equation of optimal filtering

Darouach, M.; Zasadzinski, M.; Bassong-Onana, A.;
Decision and Control, 1993., Proceedings of the 32nd IEEE Conference on , 15-17
Dec. 1993
Pages:1239 - 1240 vol.2

[Abstract]   [PDF Full-Text (164 KB)]   **IEEE CNF**

---

12 Robust nonfragile Kalman filtering for uncertain linear systems with estimator gain uncertainty
Guang-Hong Yang; Jiao Liang Wang;
Automatic Control, IEEE Transactions on , Volume: 46 , Issue: 2 , Feb. 2001
Pages:343 - 348

[Abstract]   [PDF Full-Text (212 KB)]   **IEEE JNL**

---

13 Convergence of the DRE solution to the ARE strong solution
PooGyeon Park; Kailath, T.;
Automatic Control, IEEE Transactions on , Volume: 42 , Issue: 4 , April 1997
Pages:573 - 578

[Abstract]   [PDF Full-Text (240 KB)]   **IEEE JNL**

---

14 Multiscale systems, Kalman filters, and Riccati equations
Chou, K.C.; Willsky, A.S.; Nikoukhah, R.;
Automatic Control, IEEE Transactions on , Volume: 39 , Issue: 3 , March 1994
Pages:479 - 492

[Abstract]   [PDF Full-Text (1104 KB)]   **IEEE JNL**

---

15 Cyclomonotonicity and stabilizability properties of solutions of the difference periodic Riccati equation
De Nicolao, G.;
Automatic Control, IEEE Transactions on , Volume: 37 , Issue: 9 , Sept. 1992
Pages:1405 - 1410

[Abstract]   [PDF Full-Text (556 KB)]   **IEEE JNL**

---

1 2 3 4 5 6 7 8 9 10 Next

◆IEEE

Membership   Publications/Services   Standards   Conferences   Careers/Jobs

IEEE Xplore®
RELEASE 1.7

Welcome
United States Patent and Trademark Office

IEEE *Xplore*®
1 Million Documents
1 Million Users
...And Growing

» **Search Results**

Help   FAQ   Terms   IEEE Peer Review   **Quick Links**

Welcome to IEEE Xplore®

O- Home
O- What Can
    I Access?
O- Log-out

Tables of Contents

O- Journals
   & Magazines
O- Conference
   Proceedings
O- Standards

Search

O- By Author
O- Basic
O- Advanced

Member Services

O- Join IEEE
O- Establish IEEE
   Web Account
O- Access the
   IEEE Member
   Digital Library

🖨 Print Format

Your search matched **5** of **1046194** documents.
A maximum of **500** results are displayed, **15** to a page, sorted by **Relevance** in
Descending order.

Refine This Search:
You may refine your search by editing the current search expression or entering a
new one in the text box.

vibration and disc and state   [Search]

☐ Check to search within this result set

Results Key:
JNL = Journal or Magazine   **CNF** = Conference   **STD** = Standard

---

1 **Design and analysis of a high bandwidth disk drive servo system using
an instrumented suspension**
Yuhong Huang; Banther, M.; Mathur, P.D.; Messner, W.C.;
Mechatronics, IEEE/ASME Transactions on , Volume: 4 , Issue: 2 , June 1999
Pages:196 - 206

[Abstract]   [PDF Full-Text (340 KB)]   **IEEE JNL**

---

2 **Development of a servowriter for magnetic disk storage applications**
Brown, D.H.; Sri-Jayantha, M.;
Instrumentation and Measurement, IEEE Transactions on , Volume: 39 , Issue:
2 , April 1990
Pages:409 - 415

[Abstract]   [PDF Full-Text (644 KB)]   **IEEE JNL**

---

3 **Optimal strain gauge placement for an instrumented disk drive
suspension**
Banther, M.; Yuhong Huang; Messner, W.C.;
American Control Conference, 1998. Proceedings of the 1998 , Volume: 5 , 24-26
June 1998
Pages:3023 - 3027 vol.5

[Abstract]   [PDF Full-Text (436 KB)]   **IEEE CNF**

---

4 **A programmable DSP solution to a solid state audio player**
Hayes, J.; Handley, S.; Kridner, J.; Nadeski, M.;
Consumer Electronics, IEEE Transactions on , Volume: 45 , Issue: 3 , Aug. 1999
Pages:975 - 979

5 **Identification problems in high performance microprocessor controlled electromechanical systems design**
Daubaris, G.; Kaushinis, S.; Ragauskas, A.;
Instrumentation and Measurement Technology Conference, 1992. IMTC '92., 9th IEEE , 12-14 May 1992
Pages:275 - 278

IEEE HOME | SEARCH IEEE | SHOP | WEB ACCOUNT | CONTACT IEEE   ◈IEEE

Membership   Publications/Services   Standards   Conferences   Careers/Jobs

IEEE Xplore®
RELEASE 1.7

Welcome
United States Patent and Trademark Office

IEEE Xplore®
1 Million Documents
1 Million Users
And Growing

» Search Results

Help   FAQ   Terms   IEEE Peer Review   Quick Links ▾

Welcome to IEEE Xplore

○ Home
○ What Can
   I Access?
○ Log-out

Tables of Contents

○ Journals
   & Magazines
○ Conference
   Proceedings
○ Standards

Search

○ By Author
○ Basic
○ Advanced

Member Services

○ Join IEEE
○ Establish IEEE
   Web Account
○ Access the
   IEEE Member
   Digital Library

🖨 Print Format

Your search matched **5** of **1046194** documents.
A maximum of **500** results are displayed, **15** to a page, sorted by **Relevance** in **Descending** order.

Refine This Search:
You may refine your search by editing the current search expression or entering a new one in the text box.

vibration and riccati | Search |

☐ Check to search within this result set

Results Key:
JNL = Journal or Magazine   **CNF** = Conference   **STD** = Standard

1 **Application of H∞ control to pitch autopilot of missiles**
Yang, S.M.; Huang, N.H.;
Aerospace and Electronic Systems, IEEE Transactions on , Volume: 32 , Issue: 1 , Jan. 1996
Pages:426 - 433

[Abstract]   [PDF Full-Text (616 KB)]   **IEEE JNL**

2 **Closed-loop input shaping for flexible structures using time-delay control**
Kapila, V.; Tzes, A.; Qiguo Yan;
Decision and Control, 1999. Proceedings of the 38th IEEE Conference on , Volume: 2 , 7-10 Dec. 1999
Pages:1561 - 1566 vol.2

[Abstract]   [PDF Full-Text (500 KB)]   **IEEE CNF**

3 **H∞ speed control of an induction motor with the two-mass resonant system by LMI**
Jin-Soo Kim; Young-Seok Kim; Jae-Hwa Shin; Hyun-Jung Kim;
Industrial Electronics Society, 1998. IECON '98. Proceedings of the 24th Annual Conference of the IEEE , Volume: 3 , 31 Aug.-4 Sept. 1998
Pages:1439 - 1444 vol.3

[Abstract]   [PDF Full-Text (340 KB)]   **IEEE CNF**

4 **Case studies in robust control design: an overview**
Dorato, P.;
Decision and Control, 1990., Proceedings of the 29th IEEE Conference on , 5-7 Dec. 1990

Pages:2030 - 2032 vol.4

[Abstract]   [PDF Full-Text (244 KB)]   **IEEE CNF**

5 **Convergence of infinite dimensional sampled LQR problems: theory and numerical results**
Rosen, I.G.; Wang, C.;
Decision and Control, 1989., Proceedings of the 28th IEEE Conference on , 13-15 Dec. 1989
Pages:162 - 167 vol.1

[Abstract]   [PDF Full-Text (428 KB)]   **IEEE CNF**

From: Teska, Kevin
Sent: Thursday, June 24, 2004 8:22 AM
To: Chang, Sunray; Craig, Dwin; Day, Herng-Der; Ferris, Fred; Garcia-Otero, Eduardo; Hogan, Mary; Jones, Hugh; Mehta, Arunkumar; Rosales-Hanner, Morella; Frejd, Russell; Broda, Samuel; Shaawat, Mussa; Sharon, Ayal; Stevens, Thomas H.; Phan, Thai; Thangavelu, Kandasamy; Thomson, William
Subject: FW: Orientation for experienced examiners for new PCT/ISA/237 form

EAST - [Untitled1:1]

File View Edit Tools Window Help

Drafts
Pending
Active
    L1: (192) riccati
    L2: (32) vibration and 1
    L3: (18) disc and 1
    L4: (9) 2 and 3
    L5: (9) 3 not 4
    L6: (292) state adj estimator
    L7: (17912) vibration and disc
    L8: (4494) vibration same disc
    L9: (3) 6 and 8
Failed
Saved
Favorites
Tagged (0)
UDC
Queue
Trash

	U	d	Document ID	Issue Date	Pages	Title	
1	☐	☐	US 6570730 B1	20030527	16	Shear-based transducer for HDD read/write element height control	3
2	☐	☐	US 6304409 B1	20011016	18	Active damping of actuator bearing translational mode	3
3	☐	☐	US 5668680 A	19970916	17	Time optimal control of a disc drive actuator with vibro-acoustic constraints	3

◆IEEE

IEEE *Xplore*®
RELEASE 1.7

Welcome
United States Patent and Trademark Office

IEEE *Xplore*®
1 Million Documents
1 Million Users
...And Growing

» Search Results

Help   FAQ   Terms   IEEE Peer Review   **Quick Links**

Your search matched **1** of **1046194** documents.
A maximum of **500** results are displayed, **15** to a page, sorted by **Relevance** in **Descending** order.

Refine This Search:
You may refine your search by editing the current search expression or entering a new one in the text box.

riccati and disc   **Search**

☐ Check to search within this result set

Results Key:
JNL = Journal or Magazine   **CNF** = Conference   **STD** = Standard

---

1 **Integrated optimal design of passive and active elements for hard disk servo systems**
Obinata, G.; Saito, K.; Hiramoto, K.; Doki, H.;
Control Applications, 1999. Proceedings of the 1999 IEEE International Conference on , Volume: 1 , 22-27 Aug. 1999
Pages:92 - 96 vol. 1

[Abstract]   [PDF Full-Text (316 KB)]   **IEEE CNF**

**Welcome to IEEE Xplore®**
- Home
- What Can I Access?
- Log-out

Tables of Contents
- Journals & Magazines
- Conference Proceedings
- Standards

Search
- By Author
- Basic
- Advanced

Member Services
- Join IEEE
- Establish IEEE Web Account
- Access the IEEE Member Digital Library

Print Format

http://ieeexplore.ieee.org/search/searchresult.jsp?SortField=Score&SortOrder=desc&ResultCount=15&coll1... 6/27/04

From: Teska, Kevin
Sent: Thursday, June 24, 2004 8:22 AM
To: Chang, Sunray; Craig, Dwin; Day, Herng-Der; Ferris, Fred; Garcia-Otero, Eduardo; Hogan, Mary; Jones, Hugh; Mehta, Arunkumar; Rosales-Hanner, Morella; Frejd, Russell; Broda, Samuel; Shaawat, Mussa; Sharon, Ayal; Stevens, Thomas H.; Phan, Thai; Thangavelu, Kandasamy; Thomson, William
Subject: FW: Orientation for experienced examiners for new PCT/ISA/237 form

EAST - [Untitled1:1]

File View Edit Tools Window Help

- Drafts
- Pending
- Active
  - L3: (292) state adj estimator
  - L4: (192) riccati
  - L5: (14) 3 and 4
  - L7: (4) 4 same motor
  - L6: (89) 4 and motor
  - L8: (2) 4 and vcm
- Failed
- Saved
- Favorites
- Tagged (0)
- UDC
- Queue
- Trash

	U	1	Document ID	Issue Date	Pages	Title	
1	☐	☐	US 5726879 A	19980310	39	Control apparatus, a stage apparatus and a hard disk servo writer apparatus including a robust stabilizing compensat.	7
2	☐	☐	US 5307330 A	19940426	21	Settling monitor system for a following servo	3

1

Membership   Publications/Services   Standards   Conferences   Careers/Jobs

IEEE Xplore®
RELEASE 1.7

Welcome
United States Patent and Trademark Office

IEEE *Xplore®*
1 Million Documents
1 Million Users
And Growing

Help   FAQ   Terms   IEEE Peer Review   **Quick Links**   » Search Results

Welcome to IEEE *Xplore®*

O- Home
O- What Can
    I Access?
O- Log-out

Tables of Contents

O- Journals
    & Magazines
O- Conference
    Proceedings
O- Standards

Search

O- By Author
O- Basic
O- Advanced

Member Services

O- Join IEEE
O- Establish IEEE
    Web Account

O- Access the
    IEEE Member
    Digital Library

Print Format

Your search matched **9** of **1046194** documents.
A maximum of **500** results are displayed, **15** to a page, sorted by **Relevance** in **Descending** order.

Refine This Search:
You may refine your search by editing the current search expression or entering a new one in the text box.

riccati and motor   Search

☐ Check to search within this result set

Results Key:
JNL = Journal or Magazine   **CNF** = Conference   **STD** = Standard

1 **Analytical solution for a separate state and parameter SDRE observer for a CSI-fed induction motor**
Pappano, V.; Friedland, B.;
Control Applications, 1998. Proceedings of the 1998 IEEE International Conference on , Volume: 2 , 1-4 Sept. 1998
Pages:1286 - 1291 vol.2

[Abstract]   [PDF Full-Text (436 KB)]   **IEEE CNF**

2 **The Hinf model matching approach to motor tracking control system**
Jee Ming Lee;
Industrial Automation and Control: Emerging Technologies, 1995., International IEEE/IAS Conference on , 22-27 May 1995
Pages:624 - 631

[Abstract]   [PDF Full-Text (432 KB)]   **IEEE CNF**

3 **Nonlinear state observation using H$_\infty$-filtering Riccati design**
Reif, K.; Sonnemann, F.; Unbehauen, R.;
Automatic Control, IEEE Transactions on , Volume: 44 , Issue: 1 , Jan. 1999
Pages:203 - 208

[Abstract]   [PDF Full-Text (196 KB)]   **IEEE JNL**

4 **Proceedings of the 38th IEEE Conference on Decision and Control (Cat. No.99CH36304)**

Decision and Control, 1999. Proceedings of the 38th IEEE Conference on , Volume: 1 , 7-10 Dec. 1999
[Abstract]   [PDF Full-Text (4048 KB)]   **IEEE CNF**

5 **Speed sensorless observer for an induction machine**
Pappano, V.; Friedland, B.;
American Control Conference, 1997. Proceedings of the 1997 , Volume: 6 , 4-6
June 1997
Pages:3805 - 3806 vol.6

[Abstract]   [PDF Full-Text (136 KB)]   **IEEE CNF**

6 **H$_\infty$ speed control of an induction motor with the two-mass resonant system by LMI**
Jin-Soo Kim; Young-Seok Kim; Jae-Hwa Shin; Hyun-Jung Kim;
Industrial Electronics Society, 1998. IECON '98. Proceedings of the 24th Annual
Conference of the IEEE , Volume: 3 , 31 Aug.-4 Sept. 1998
Pages:1439 - 1444 vol.3

[Abstract]   [PDF Full-Text (340 KB)]   **IEEE CNF**

7 **Optimal location of measurements for distributed parameter estimation**
Kumar, S.; Seinfeld, J.;
Automatic Control, IEEE Transactions on , Volume: 23 , Issue: 4 , Aug 1978
Pages:690 - 698

[Abstract]   [PDF Full-Text (848 KB)]   **IEEE JNL**

8 **Multivariable bilinear vehicle control using steering and individual wheel torques**
Langson, W.; Alleyne, A.;
American Control Conference, 1997. Proceedings of the 1997 , Volume: 2 , 4-6
June 1997
Pages:1136 - 1140 vol.2

[Abstract]   [PDF Full-Text (332 KB)]   **IEEE CNF**

9 **Synthesis of optimal sliding mode control for robust DC drive**
Zhang, J.; Chan, W.C.; Wang, A.; Barton, T.H.;
Industry Applications Society Annual Meeting, 1988., Conference Record of the
1988 IEEE , 2-7 Oct. 1988
Pages:535 - 542 vol.1

[Abstract]   [PDF Full-Text (344 KB)]   **IEEE CNF**

◈IEEE

Membership   Publications/Services   Standards   Conferences   Careers/Jobs

IEEE *Xplore*®
RELEASE 1.7

Welcome
United States Patent and Trademark Office

IEEE *Xplore*®
1 Million Documents
1 Million Users
...And Growing

» **Search Results**

Help   FAQ   Terms   IEEE Peer Review

Quick Links   ▽

Welcome to IEEE *Xplore*®

○- Home
○- What Can
   I Access?
○- Log-out

Tables of Contents

○- Journals
   & Magazines
○- Conference
   Proceedings
○- Standards

Search

○- By Author
○- Basic
○- Advanced

Member Services

○- Join IEEE
○- Establish IEEE
   Web Account
○- Access the
   IEEE Member
   Digital Library

🖨 Print Format

Your search matched **6** of **1046194** documents.
A maximum of **500** results are displayed, **15** to a page, sorted by **Relevance** in **Descending** order.

Refine This Search:
You may refine your search by editing the current search expression or entering a new one in the text box.

riccati and state estimator | **Search** |

☐ Check to search within this result set

Results Key:
JNL = Journal or Magazine   **CNF** = Conference   **STD** = Standard

---

1 **Robust H_2/H_∞-state estimation for systems with error variance constraints: the continuous-time case**
Zidong Wang; Unbehauen, H.;
Automatic Control, IEEE Transactions on , Volume: 44 , Issue: 5 , May 1999
Pages:1061 - 1065

[Abstract]   [PDF Full-Text (144 KB)]   **IEEE JNL**

---

2 **Model validation and state estimation for uncertain continuous-time systems with missing discrete-continuous data**
Savkin, A.V.; Petersen, I.R.;
Decision and Control, 1996., Proceedings of the 35th IEEE , Volume: 1 , 11-13 Dec. 1996
Pages:570 - 573 vol.1

[Abstract]   [PDF Full-Text (388 KB)]   **IEEE CNF**

---

3 **Stochastic optimal control under randomly varying distributed delays**
Nan-Chyuan Tsai; Ray, A.;
Decision and Control, 1996., Proceedings of the 35th IEEE , Volume: 1 , 11-13 Dec. 1996
Pages:650 - 655 vol.1

[Abstract]   [PDF Full-Text (424 KB)]   **IEEE CNF**

---

4 **Kalman filtering for continuous-time uncertain systems with Markovian jumping parameters**
Peng Shi; Boukas, El.-K.; Agarwal, R.K.;
Automatic Control, IEEE Transactions on , Volume: 44 , Issue: 8 , Aug. 1999
Pages:1592 - 1597

[Abstract]   [PDF Full-Text (192 KB)]   **IEEE JNL**

---

5 **The extended Kalman filter as an exponential observer for nonlinear systems**
Reif, K.; Unbehauen, R.;
Signal Processing, IEEE Transactions on [see also Acoustics, Speech, and Signal Processing, IEEE Transactions on] , Volume: 47 , Issue: 8 , Aug. 1999
Pages:2324 - 2328

[Abstract]   [PDF Full-Text (132 KB)]   **IEEE JNL**

---

6 **Robust Kalman filtering for continuous-time Markovian jump uncertain systems**
Peng Shi; Boukas, E.-K.; Agarwal, R.K.;
American Control Conference, 1999. Proceedings of the 1999 , Volume: 6 , 2-4 June 1999
Pages:4413 - 4417 vol.6

[Abstract]   [PDF Full-Text (408 KB)]   **IEEE CNF**

◆IEEE

Membership Publications/Services Standards Conferences Careers/Jobs

IEEE *Xplore*®
RELEASE 1.8

Welcome
United States Patent and Trademark Office

IEEE *Xplore*®
1 Million Documents
1 Million Users

» ABSTRACT PLUS

Help   FAQ   Terms   IEEE Peer Review

Quick Links

Welcome to IEEE *Xplore*®

○ Home
○ What Can
   I Access?
○ Log-out

Tables of Contents

○ Journals
   & Magazines
○ Conference
   Proceedings
○ Standards

Search

○ By Author
○ Basic
○ Advanced

Member Services

○ Join IEEE
○ Establish IEEE
   Web Account
○ Access the
   IEEE Member
   Digital Library

IEEE Enterprise

○ Access the
   IEEE Enterprise
   File Cabinet

🖶 Print Format

Search Results   [PDF FULL-TEXT 432 KB]   DOWNLOAD CITATION

Request Permissions
RIGHTSLINK◊

The Hinf model matching approach to motor tracking control system

Jee Ming Lee
Dept. of Electr. Eng., Nat. TaipeiInst. of Technol., Taipei, Taiwan;
This paper appears in: **Industrial Automation and Control: Emerging Technologies, 1995., International IEEE/IAS Conference on**

Abstract:
The H^∞ model matching algorithm is proposed for the robust motor tracking control of linear time-varying multi-input, single-output uncertain system. This control method is verified by the system of the permanent magnet DC motor to improve the drive performance and reduce sensitivity of parameter variations, nonlinear effects, and other disturbances such as load changes and backlash. The matching model is used to identify the H^∞ tuning controller with bounded noise energy and minimized tracking error. An algorithm based on discrete Ricatti equation and H^∞ interpolation theory is used to solve the uncertain internal modeling and noise measurement issues in the tracking control system. The adaptive tuning controller effectively controls the presence of external disturbances, and identifies the rapid jumping and slow changing trajectory of the system. The effectiveness of the H^∞ model matching controller for the motor tracking control system is demonstrated by using the developed H^∞ adaptive tuning software controller. The H^∞ model matching control method is examined through computer simulation, and then tested in a real time microprocessor-controlled drive system. Experimental results based on PC based microcomputer implementation are presented to illustrate improved response and robust performance

Index Terms:
DC motor drives H_∞ control H_∞ interpolation theory H_∞ model matching algorithm
H_∞ tuning controller   MISO system   PC-based microcomputer implementation   **Riccati**

equations   adaptive tuning controller   bounded noise energy   discrete **Riccati** equation   interpolation   linear time-varying multi-input single-output uncertain system   machine control   minimized tracking error   model reference adaptive control systems   multivariable control systems   noise measurement   nonlinear effects   parameter variations   permanent magnet DC motor   permanent magnet motors   real-time microprocessor-controlled drive system   robust control   robust motor tracking control   sensitivity reduction   time-varying systems   uncertain internal modeling   uncertain systems   DC motor drives H_{∞} control H_{∞} interpolation theory H_{∞} model matching algorithm H_{∞} tuning controller   MISO system   PC-based microcomputer implementation   **Riccati** equations   adaptive tuning controller   bounded noise energy   discrete **Riccati** equation   interpolation   linear time-varying multi-input single-output uncertain system   machine control   minimized tracking error   model reference adaptive control systems   multivariable control systems   noise measurement   nonlinear effects   parameter variations   permanent magnet DC motor   permanent magnet motors   real-time microprocessor-controlled drive system   robust control   robust motor tracking control   sensitivity reduction   time-varying systems   uncertain internal modeling   uncertain systems

Documents that cite this document
There are no citing documents available in IEEE Xplore at this time.

Search Results   [PDF FULL-TEXT 432 KB]   DOWNLOAD CITATION

Home | Log-out | Journals | Conference Proceedings | Standards | Search by Author | Basic Search | Advanced Search | Join IEEE | Web Account | New this week | OPAC Linking Information | Your Feedback | Technical Support | Email Alerting | No Robots Please | Release Notes | IEEE Online Publications | Help | FAQ| Terms | Back to Top

The Hinf Model Matching Approach to
Motor Tracking Control System

JeeMing Lee
Department of Electrical Engineering
National Taipei Institute of Technology

ABSTRACT

The H^∞ model matching algorithm is proposed for the robust motor tracking control of linear time-varying multi-input, single-output uncertain system. This control method is verified by the system of the permanent magnet DC motor to improve the drive performance and reduce sensitivity of parameter variations, nonlinear effects, and other disturbances such as load changes and backlash. The matching model is used to identify the H^∞ tuning controller with bounded noise energy and minimized tracking error. An algorithm based on discrete Ricatti equation and H^∞ interpolation theory is used to solve the uncertain internal modeling and noise measurement issues in the tracking control system. The adaptive tuning controller effectively controls the presence of external disturbances, and identifies the rapid jumping and slow changing trajectory of the system. The effectiveness of the H^∞ model matching controller for the motor tracking control system is demonstrated by using the developed H^∞ adaptive tuning software controller. The H^∞ model matching control method is examined through computer simulation, and then tested in a real time microprocessor-controlled drive system. Experimental results based on PC based microcomputer implementation are presented to illustrate improved response and robust performance.

Keywords: H^∞ model matching, tracking control system, bounded noise, adaptive tuning.

I. INTRODUCTION

Following the output of a system track from a given reference trajectory is a common industrial problem.

Sometimes the mechanical load varies considerably, but the trajectory of the motor drive still has to follow the required tracking operation. These situations can be found in typical examples, such as: robot joints, and machine tools[1][2][8][9][10]. All these motion systems require the motor bore the load changing and still keep the prescribed trajectory.

The motion disturbance in the above description accords to the uncertainty noise under modeling system which has to be minimized. It is the aim to make the motor drive system to meet the robust stability of control performance. And in order to obtain the satisfactory tracking performance[7], the adaptive tuning controller is usually considered in the linear on-line control strategy for a successful application[1]. However, it needs to design a reasonably accuracy model, or the resulting control algorithm is hard to maintain the tracking system in the robust stability. Envisioned the performance exploited by robust stable modeling operation in the sense, it is believed that the controller should be designed to have abilities to bound the noise disturbance and minimize the tracking error.

In this paper, a motor tracking control design using H^∞ model matching is proposed. It is designed to exclude the noise spectral densities whereas the conventional approaches can not. The merits of the approach lie in the simplicity of the scheme and its practicality for real-time implementation.

The identification has to be carried out within internal model matching condition. In order to make sure that a control transient can be concluded already with the desired response, the identification and the adaptation of the controllers have to be performed as fast as possible. The limited time needed for updating the controllers is determined by the convergence time of the identification algorithm and the time needed to calculate the new controller setting.

Generally, electrical drives are nonlinear systems because of current, voltage and speed boundaries. In addition, their parameters, e.g. resistance, inductance, moment of inertia, can vary. Also in real drive systems, the disturbances, e.g. load torque on the motor shaft, must be considered. The non-linearity of load torque and mechanical dampers is the main factors to make the tracking misalignment and system unstable[7]. In this paper, the system model of permanent-magnet DC motor is adopted to verify the tracking performance and robust stability.

Fig.1-1 is the block scheme diagram of main sections. Brushless dc motor represents in the dotted box. Inverted commutation circuit shows within the dashed line. The others of the diagram are included with the controller. Two input signals of the system from the current sensing which is proportional to the motor voltage and the increment encoder determine the rotor position.


Fig.1-1 The hardware scheme diagram of motor main system

II. DYNAMIC MODEL OF PERMANENT MAGNET MOTOR DRIVE SYSTEM

The permanent magnet motor drive can be regarded as direct current by having d-q axes transformation that rotates synchronously with the alternating current. Because the relative velocity between the rotor shaft and

stator becomes zero, making the dynamic model simpler. The relationship between voltage and current of a permanent magnet motor drive is as follows:

$$\begin{bmatrix} E_d \\ E_q \end{bmatrix} = \begin{bmatrix} R_a + p\,L_a & -\omega_m L_a \\ \omega_m L_a & R_a + p\,L_a \end{bmatrix} \begin{bmatrix} i_d \\ i_q \end{bmatrix} + \begin{bmatrix} \omega_m \phi \\ 0 \end{bmatrix} \quad (2\text{-}1)$$

Usually, i_q make the minor effect in the controlled motor system. Therefore, the i_d current of the motor produce the strong control factor in the system. From eqn (2-1) E_d, E_q are the motor's terminal voltage in the steady state. The dynamic electrical circuit model is derived as:

$$d\,i_d/dt = -R_a/L_a\,i_d - \phi\,\omega_m/L_a + E_d/L_a \quad (2\text{-}2)$$

The instantaneous torque T_l is

$$T_l = J_l\,\dot{\omega}_m + B_m\omega_m + k\phi i_d \quad (2\text{-}3)$$

The system parameter is described as follows:

R_a : the armature resistance
L_a : the armature inductance
J_l : the motor moment of inertia
ϕ : the magnetic flux of the permanent magnet (constant).
w_m : the angular velocity of the motor
B_m : the coefficient of viscous friction
$p = d/dt$
T_l : the load torque
E_d, E_q, i_d and i_q are d, q shaft voltages and currents.

From eqn (2-2) and (2-3) the transfer function of the permanent magnet motor drive with the variable disturbance load is shown in Fig.2-1.

The dynamic model of permanent magnet DC motor is well established in the continuous time domain by the state space model[13]:

$$\dot{x}(t) = \underline{A}x(t) + \underline{B}U(t) \quad (2\text{-}4)$$

where

$$x(t) = \begin{bmatrix} \theta_m(t) & \omega_m(t) & i_d(t) & i_q(t) \end{bmatrix}$$

$$U(t) = \begin{bmatrix} T_l(t) & E_d(t) & E_q(t) \end{bmatrix}$$

$$\underline{A} = \begin{bmatrix} 0 & 1 & 0 & 0 \\ 0 & -B_m/J_l & k_T/J_l & 0 \\ 0 & k_E/L_a & -R_a/L_a & 0 \\ 0 & 0 & 0 & -R_a/L_a \end{bmatrix}$$

$$\underline{B} = \begin{bmatrix} 0 & 0 & 0 \\ -1/J_l & 0 & 0 \\ 0 & 1/L_a & 0 \\ 0 & 0 & -1/L_a \end{bmatrix}$$

where
$x(t)$ = state vector of the motor components.

U(t) = the disturbance (load torque) and the control signal (voltage)

A and B are system matrices corresponding to the input/output vectors, respectively.


Fig. 2-1   Block diagram of a brushless DC motor

To protect the motor from overload in the motor tracking system. The motor system has specified constraints on the motor current. These limitations are as follows[2][7][11]:

(1) Peak current limitation: The maximum occurring motor is limited to avoid demagnetization of the permanent magnets.

(2) Continuous current limitation: To prevent the motor from overheating. the maximum constant current is limited to approximately half the peak current for the motor used. The continuous current limitation becomes active only after a certain period of time and can be disregarded in position control. However, if torque control is used. longer periods of maximum applied power can occur; in this case. the continuous current limited is important for the prevention of the power capacity of the driver components.

(3) Commutation limitation: The inrush current through the power drive components increases with the motor speed and the heavy load variation. To prevent the motor from being damaged, the product of armature current and voltage is limited.

In this paper. however, a systematic method is proposed to determine the plant orders and time delay of the motor tracking system[1][17]. To derive the computation equations, the time domain model of PM machine with a controller is transformed into the the discrete model in the z domain form. and generates the system upper bound for the worse case, as well as robust tracking output. The system is specified the requirement as followings:

speed bandwidth: 0 - 50Hz , under load condition and 12.5Hz for loading variation. The robustness is as large as possible within the setting frequency response. The accuracy of the position is within 1um, and no exciting phenomenon. Insensitivity of load disturbance and noisy

interference is designed in the adaptive control scheme and modeling matching.

III. THE H^∞ SYNTHESIS CONTROL CONCEPTS

First, the H^∞ synthesis control system is structured as a standard problem, depicted in Figure 3-1. where the objective is to design a real-rational proper controller K such that the closed-loop system formed by real rational proper G and K is internally stable and the H^∞ norm of the transfer function between external input vector v and controlled output vector z is minimized over all stabilizing controllers[3].


Fig. 3-1 H^∞ synthesis standard problem

w : exogenous input vector included disturbance d. noise n, and reference order r.

z : controlled output vector included tracking error z_e, energy z_g, and output tracking z_t.

y : observed measured output vector.

u : controlled input state.

G : The augmented control model.

K : The feedback controller.

This augmented control system G can be written as:

$$G : G = C(qI - A)^{-1}B + D \tag{3-1}$$

The synthesis system can be represented as:

$$\begin{bmatrix} G_{11} & G_{12} \\ G_{21} & G_{22} \end{bmatrix}\begin{bmatrix} w \\ u \end{bmatrix} = \begin{bmatrix} z \\ y \end{bmatrix} \tag{3-2}$$

Setting the system gain K for feedback as:

$$u = Ky \tag{3-3}$$

The convergence and stability of the system can be obtained from inputs w to the outputs z of the close loop function. The form is expressed as:

$$z = T_{zw}(G, K)w \tag{3-4}$$

$$T_{zw} = G_{11} + G_{12}K(I - G_{22}K)^{-1}G_{21} \tag{3-5}$$

Eqn(3-5) represents the standard form of H$^\infty$ synthesis control system. The augmented synthesis system has to find the controller K so that

$$\inf_{K} \| G_{11} + G_{12}K(J - G_{22}K)^{-1} G_{21} \|_{\infty} \qquad (3-6)$$

The controller K [4] has to satisfy the following two conditions:

(i) The closed loop system is internally stable.

(ii) $\min \| T_{nw}(G,K) \|_{\infty} < \gamma \qquad 0 < \gamma < 1$

The augmented control system G means the combination of the real control system P and filter functions AW for the tracking error and the internal system entropy. The filter function we adopt in this article shall consider the response of the output tracking as well as the minimized sensitivity for the system stability thereby boosting the system's performance and robustness.

The synthesis H$^\infty$ system is examined in reconstruction state space forms[5][6]. The mean square reconstruction error value is to measure the observer's reconstruction status. To design a time varying tuning procedure as follows:

$$Q(n+1) = \hat{A}(n)Q(n)\hat{A}^T(n) + W_1(n)$$
$$\text{(pre-covariance)} \qquad (3-7)$$

$$L(n+1) = Q(n+1)\hat{C}^T(n+1)[\hat{C}(n+1)Q(n)\hat{C}^T(n+1) + W_2]^{-1} \quad \text{(state estimation gain)} \quad (3-8)$$

$$Q(n+1) = [I - L(n+1)\hat{C}(n+1)]Q(n)$$
$$\text{(observed covariance)} \qquad (3-9)$$

From the above adaptive procedure, the synthesis H$^\infty$ system shall be examined from the predictor-corrector state.

$$\hat{x}(n+1) = \hat{A}(n)\hat{x}(n) + \hat{B}(n)u(n) + L(n+1)\{ y(n+1) - \hat{C}(n)[\hat{A}(n)\hat{x}(n) + \hat{B}(n)u(n)]\} \quad (3-10)$$

IV. THE ADAPTIVE MODELING IDENTIFICATION

The dynamic model of PM DC motor is well set up by the augmented system that is translated into the difference equation necessary for use in the discrete system[15].

The discrete form is given by eqn (4-1) in the state space model:

$$\bar{y}_t = \bar{A}(n-1)\bar{x}(n-1) + \bar{B}(n-1)\bar{u}(n-1) \qquad (4-1)$$

The matrices $\bar{A}(n-1)$, and $\bar{B}(n-1)$ in discrete-time model are based on the motor's parameters in eqn (2-4).

The approach to make the identification of a motor trajectory employs the QR based method to solve the recursive least square(RLS) problem. The QR based method is numerically stable. It shows that the

computation method of matrix problems is for orthogonal similarity transformation.

To do so in the adaptive tuning procedure[17], the objective is to finally obtain a predictor model for the desired tracking y_t:

$$y_t(n) = X^T(n) \theta(n) + \zeta_t \qquad (4-1)$$

where $X^T(t)$ is an observed vector using past values of y_t and X. $\theta(t)$ is a parameter vector using the coefficients from the above of $A(n-1)$ and $B(n-1)$, and ζ_t is an error variable representing the load disturbance and modeling error. From the QR based least squares computation, it is to see that generation of pseudo-linear variable y_t, defined as

$$y'_t = T^{-1} AT \cdot X(n) \qquad (4-2)$$

The setting up recursive least square (RLS) model, keep the identification order low. A state space predictor for the plant model[14] can now be set up by a series of estimation steps.

$$\text{error:} \qquad e_t = y'_t - X(n)\hat{\theta}(n) \qquad (4-3)$$

controller gain:
$$K_t(n) = -[\hat{B}^T P_{t-1}(n)\hat{B} + \lambda_{t-1}(n)]^{-1} \hat{B}^T P_{t-1}(n)\hat{A} \qquad (4-4)$$

$$\text{estimate:} \quad \hat{\theta}_t(n) = \hat{\theta}_{t-1}(n) + K_{t-1}(n)e_t \qquad (4-5)$$

forgetting factor:
$$\lambda_t(n) = I - (I + \hat{B}^T P_{t-1}(n)\hat{B})e_t^2 / \Gamma \qquad (4-6)$$

covariance:
$$P_t(n) = [\hat{A} + \hat{B}K_t(n)]^T P_{t-1}(n)[\hat{A} + \hat{B}K_t(n)] + K_t^T(n)\lambda_t(n)K_t(n) \qquad (4-7)$$

$P_t(n)$ has to be positive semidefinite, and if $P_t(n)$ has rank defect r, then it needs to use an orthogonal transformation T to adjust it.

V. The Model Matching for the Motor System

The estimator of the system is reconstructed after every periodic computation. It consists of a set of time varying equations from eEqn (3-7) to eqn (3-10). These works can form an estimated system model. The controller of the augmented system is designed in accordance with eqn (4-2) to eqn (4-7). It executes in the state of the adaptive tuning to minimize the motor tracking error.

The H$^\infty$ approach design is needed to specify the disturbance from the input for the worse case. Therefore, the term gamma γ is required to setup for the robust range.

$$\sigma(P_t(n)Q(n)) < \gamma^2 \qquad (5-1)$$

Fig. 5-1: The H^∞ synthesis model control system

It means that the spectral radius of $P_i(n)Q(n)$ must be lower than the upper bound of disturbance γ.

Fig.5-1 shows the H^∞ synthesis control scheme model for the motor control system. From the figure 5-1 the estimated system model is derived from the real motor system and the desired augmented reference plant. The adaptive H^∞ controller is designed after the system model [16] is estimated.

VI. TEST RESULTS

Several test cases in the experiment evaluate the proposed H^∞ approach model matching technique.

The position track selected in this test is composed of three segments of sigmoidal functions. The first rotates the forward position by 200 radian, the second is holding the position at 200 radian for 2 second, and the third turns the reverse direction back to the original position by the armature current braking from the feedback sensor signal. In these test cases, the armature surge current is limited within the specified range to verify the motor system running within the designed tracking and safety working condition.

Two cases are shown on the following mainly to represent the trajectories of the motor rotor position and required speed tracking paths. Each of the motor system tracking is measured from the starting time and sampled in every 20 msec.

Case I shows figures from Fig.6-1 to Fig.6-10 to examine the motor system performance and robust. Case I represents 10% perturbation with the required trajectory entering the motor system and the load torque changing periodically every 12.5Hz. Figure 6-1 to 6-7 shows the tracks and the measurements of the rotor position, speed, voltage, and electric torque, position tolerance, direct current, and quardrature current, respectively. The

dotted line on Fig. 6-1 and Fig. 6-2 represents the desired trajectory, while the the dash line represents the output trajectory. The position trajectory follows the desired sigmoidal tracking on Fig. 6-1. The speed trajectory gets some disturbance but still maintain the set speed


Fig. 6-1   Case I: Position trajectory


Fig. 6-2   Case I: Speed trajectory


Fig. 6-3   Case I: Position tolerance


Fig. 6-4   Case I: Electric torque

Figure 6-5   Case I: Armature voltage

Fig. 6-6   Case I: Direct current


Fig. 6-7   Case I: Quardrature current

Fig. 6-8   Case I: Parameters of $\bar{A}$(q)

Fig. 6-9   Case I: Parameters of $\bar{B}$(q)

Fig. 6-10   Case I: Parameter of $\bar{C}$(q)

running on Fig.6-2. Fig. 6-4 shows the electric torque increased during the motor accelerating the speed. However, the motor system still maintains in the safe running condition by examining the voltage and current variation from Fig. 6-5 to Fig. 6-7.

The time varying motor system under the noise perturbation and load change highly depends on the adaptive tuning for the satble and robust synthesis system performance. Fig. 6-8 to Fig. 6-10 show the synthesis parameters of the H^∞ system. The parameters of matrices of $\bar{A}$(q), $\bar{B}$(q) and $\bar{C}$(q) show the adaptive identification for the reduction order H^∞ approach matching. Specifically, when the motor proceeds the tracking in the braking segment, the system parameters vary quite largely.

To satify the robust performance of the H^∞ synthesis approach, it is designed the upper bound for the worse case at the gamma value (γ) 0.67 in Case I.

Case II represents the situation of the 50% uniform distributed perturbation with the desired trajectory entering the motor system and the load torque changing periodically every 25Hz. Fig. 6-11 to Fig. 6-15 shows the performance of the motor system in case II. It examines the motor system with the robust control In the H^∞ synthesis approach. In Case II. the gamma term γ is designed 0.45 for the robust range. It can meet the case to limit the upper bound of disturbance.

Figure 6-11   Case II·   Position trajectory

Fig. 6-15   Case II: Electric torque

Fig. 6-12   Case II: Speed trajectory


Figure 6-13   Case II: Position tolerance

Fig. 6-14   Case II·   Armature voltage

The dotted line on Fig. 6-11 and Fig. 6-12 represents the desired trajectory. while the the dash line represents the output trajectory.   Fig. 6-11 shows the position trajectory following the desired tracking under the heavy

noise and load varying.   It can be seen from Fig. 6-13 that the position trajectory has one step predicted error, especially, during the motor increasing speed. However, the dc error of the position trajectory is derived from the uncertainty disturbance. It can be compensated to adjust the deadbeat of the filter.

In this paper, it mainly emphasizes the performance of the position trajectory.   Therefore. the speed trajectoryon Fig. 6-12 is infected by some disturbance similarly as Case I, during the motor starting, speedup, and braking stop. Fig. 14 and Fig. 15 show the motor system still stable when the strong perturbation adds to the system. In Case II it still can work within the protected safty range.

Fig. 6-13 shows that the larger position tolerance appears as the disturbance become larger, comparing with Case I. It shows that the dc tolerance is reduced by adding the constant backlash. However, it is designed from the synthesis system to bound the disturbance in the spectral radius.

VII.   CONCLUSIONS

In this paper, the design and implementation of an H^{∞} matching controller with an adaptive tuning has been investigated.   A synthesis systematic and analysis approach for developing the algorithm is presented. The H^{∞} filter is tuned by various parameters $Q(n), L(n), K(n), \lambda(n), P_i(n), and \; X(n)$ which   are dominant in the state identified model and the designed H^{∞} controller.   These parameters have to meet the desired transient and steady state performance. The discrete adaptive H^{∞} matching controller has been designed to be well suited the motor speed and position trajectory for Brushless DC motor. The load torque variation and mechanical damper can be immunize by the designed H^{∞} controller under the upper bound area. The next step in this research will test the H^{∞} matching

controller in different kinds of disturbance for the speed and position trajectory.

REFERENCES

[1] JeeMing Lee, "Motor Drive Control System for Education and Research,"IEEE Power Electronics and Drive Systems, PEDS'95 in Singapore, 1995.

[2] JeeMing Lee, "Training Tool for Industrial Real-Time Automatic Control Engineering," The 3rd International Automatic Control Engineering in Taiwan, Vol.6, pp.23-30, 1994.

[3] P Coustal and J.M. Michelin, "Industrial Application of an H-Infinity Design Method for Flexible Structures," IEEE Control Systems, pp.49-54, Aug. 1994.

[4] J.C. Doyle, K. Glover, P.P. Khargonekar, and B.A. Francis, "State-Space Solutions to Standard H2 and Hinf Control Problems," IEEE Trans. on Automatic Control, Vol.34, No.8, pp.831-847, Aug. 1989.

[5] Craig Barratt and Stephen Boyd, "Example of Exact Trade-offs in Linear Controller Design," IEEE Control Systems, pp.46-52, Jan. 1989.

[6] U Shaked, "H∞- Minimum Error State Estimation of Linear Stationary Processes," IEEE Trans. on Automatic Control, Vol. 35, No.5, pp. 554-558, May 1990

[7] Y. Dote, "Brushless Servomotor Control," Printice-Hall, pp. 104-169, 1990.

[8] M.A. El-Sharkawi and S. Weerasooriya, "Development and Implementation of Self-Tuning Tracking Controller for DC Motors," IEEE Trans. on Energy Conversion, pp. 122-128, March 1990.

[9] S. Weerasooriya and M.A. El-Sharkawi, "Adaptive Tracking Control for High Performance DC Drives," IEEE Trans. on Energy Conversion, pp.502-508, Sep. 1989.

[10] Chuan-Kun Wang, and Ying-Yu Tzou, "Single-Chip DSP-Based Biaxial AC Drive with Coordinated Motion Control," Proceedings of the 15th Symposium on Electrical Power Engineering, pp.200-205, Dec. 1994.

[11] K. Ishida, K. Nakamura, T. Izumi, and M. Ohara from Fuji Electric Co., "Microprocessor Control of Converter-Fed DC motor Drives," IEEE/IAS Annual Meeting, pp.619-623, 1982.

[12] D. Naunin, D. Hetzel, H.C. Reuss, and C. Sechelmann, "Completely Digital Position Feedback Control for Synchronous Servodrives," IEEE/IAS Annual Meeting, pp.452-459, 1989.

[13] P.C. Krause, and O. Wasynczuk, "Electromechanical Motion Devices," McGraw-Hill, pp.273-328, 1989.

[14] R. Dhaouadi, Ned Mohan, and L. Norum, "Design and Implementation of an Extended Kalman Filter for the State Estimation of a Permanent Magnet Synchronous Motor," IEEE Proceedings of Power Electronic Specialists Conference, pp. 355-362, June 1990.

[15] N. Matsui and H. Ohashi, "DSP-Based Adaptive Control of a Brushless Motor," IEEE Industry Applications Conference, pp. 329-334, 1988.

[16] S.M. Veres and J.P. Norton, "Bound-Based Worst-Case Predictive Controller," IFAC Intelligent Tuning and Adaptive Control, pp.229-234, Singapore 1991.

[17] T. Suehiro, F. Ohkawa, K. Kurosu, and T. Yamashita, "Adaptive Control for a Robot Arm and a Robot Drive System with Elasticity," IFAC Intelligent Tuning and Adaptive Control, pp. 199-204, Singapore 1991.